

PILOMAT 355/PF 600F

FIXED PILOMAT

The fixed 355/PF 600F PILOMAT have been designed and built with architectural appearence similar to that of the mobile PILOMAT and therefore also allows the combined use of both versions. The current models are the result of the development of more than 15 years of experience.



GENERAL FEATURES

The fixed PILOMAT are used in public or private areas in order to define or prevent the parking of vehicles, for preventing access to vehicles in pedestrian areas.

- **PF SERIES:** These items can be cemented to the ground (in this case, the resistance to breakage depends on the depth to which it is anchored into the ground) or be secured in place by chemical anchors in places where you cannot make the same anchor, or where masonry is already completed.
- Choice of optional configurations:
 - FE370 or AISI 304 stainless steel moving cylinders
 - custom colours
 - flashing lights integrated in the head.

FIXED CYLINDER	FE 370 STEEL (IRON)
FIXED CYLINDER NOMINAL DIAMETER	355 mm
FIXED CYLINDER HEIGHT	600 mm
FIXED CYLINDER FE 370 STEEL THICKNESS	6 mm
FIXED CYLINDER STAINLESS STEEL THICKNESS	-
FIXED CYLINDER FE 370 STEEL FINISH	POLYESTER POWDER PAINT - STANDARD GREY ANTHRACITE
FIXED CYLINDER STAINLESS STEEL FINISH	-
REFLECTING ADHESIVE STRIP	YES - HEIGHT 55 mm
IMPACT RESISTANCE (WITHOUT DEFORMATION)	40.000 J
BREAKOUT RESISTANCE	200.000 J