



BIONIK SERIES

THE BRUSHLESS AUTOMATED BARRIER
WITH DIGITAL THINKING



WHAT WE DO

INNOVATION, TOP NOTCH MECHANICS AND NEVER-ENDING TECHNOLOGICAL RESEARCH ARE THE ELEMENTS THAT MAKE ROGER TECHNOLOGY A UNIQUE AND DIFFERENT COMPANY

Starting from our first day of work we immediately gave priority to the development and production of excellent, completely Italian mechanics, based only on top quality ferrous and non ferrous raw materials and guaranteed by impeccable production and surface treatment processes. It was just a few years later, starting in the 1990s, that we created the first major step in our history, by implementing a real mass production line for completely robotised motors, thus becoming a reference outsourcer for major brands of the gate automation market.

PEOPLE, IDEAS AND PRODUCT EXPERIENCE

From the very beginning Roger Technology has evolved and grown because it's people believe that any bright idea can lead to great change in the future. Our people are passionate and innovative in our approach to every challenge, allways pushing the boundaries to develop extraordinary products.

In our language we translate the word "experience" as passion. It is this passion that drives us in the development of revolutionary **new products** that serve the real needs of our customers. We understand that our customers want a product designed around the way that they work.

*Primo Florian
Founding partner
Engineering
and design*

*Dino Florian
Founding President
Development
and design*

*Renato Florian
Founding partner
Assembly
and quality*



OUR PLUSES

EXCELLENT RAW MATERIALS

Steel, ductile cast iron, aluminium, bronze, copper and titanium have always been the main and exclusive raw materials used in the advanced engineering processes of our company.



PRODUCTION TECHNOLOGY

At Roger Technology all internal manufacturing is carried out on optimised production lines making use of very advanced technology. We have invested heavily in robotics and automated all product manufacturing phases. This ensures that all components and semi-finished products are highly reliable and are fully compliant with our exceptionally high quality standards.



INTERNAL ASSEMBLY

Our highly qualified and dedicated staff oversee the fitting and assembly stages. Every piece of equipment is checked by our all italian personnel to ensure that we deliver reliable products to our customers.



MADE IN ITALY

All solutions, products, design and the complete production process of Roger Technology is developed in Italy with the use of materials of primary quality always found in the market trough partner suppliers that share the same passion and professionalism of our company in developing products technologically reliable, efficient and simple in the way that they have been made for being installed and used.



BRUSHLESS MOTOR

A DIGITAL BRUSHLESS MOTOR WITH PERMANENT MAGNETIC FIELD, DIGITAL ELECTRONICS FOR THE COMPLETE MANAGEMENT OF THE AUTOMATION SYSTEM CONTROL. DESIGNED FOR SUPER INTENSIVE USE WITH THE ADDED BENEFIT OF A SUPER LOW POWER CONSUMPTION: THIS IS ROGER BRUSHLESS

We are the creators at the heart of the product!
All of our digital brushless motors are designed and manufactured in our own factories. Using dedicated automated machines the motors are wound with ultimate precision.

DIGITAL BRUSHLESS MOTOR

Revolutionary and innovative digital Brushless motor with permanent magnetic field, three-phase sinusoidal power supply with native encoder that allows super-intensive use of the automation system with extremely low power consumption, not only providing 100% compliance with all the automation system management and safety rules, but setting new standards in gate safety.


NEW GENERATION OF ELECTRONICS

The new control unit with onboard digital Brushless controller. Without traditional relays and due to the revolutionary MOSFET quadrant system and its control technology entirely based on a DSP (Digital Signal Processor) microcontroller, it represents a new generation of electronic cards created to safely handle all movement phases of the automation system.

ENGINEERING PASSION

All the mechanical components and gears are manufactured in steel, cast iron and bronze. The automation system casings are made from titanium-reinforced die-cast aluminium. All the gears are inspected and assembled on high-quality bearings and inserted on precise seats machined to provide absolute precision between the axes.

A TECHNOLOGY THAT OFFERS MAXIMUM PERFORMANCE BUT CONSUMES LESS POWER THAN OTHER MOTORS



5

COMPLETELY BRUSHLESS

THE REVOLUTIONARY DIGITAL MOTOR WITH 12 UNIQUE FEATURES



3-PHASE DIGITAL BRUSHLESS MOTOR

A very powerful motor with substantial torque. The motor is compact and neat due to the special concentrated coil windings, it is powered by a **three phase sinusoidal system**.



NO PROBLEM IN THE EVENT OF POWER FAILURE

With the help of internal or external batteries and the associated battery charging card, your automation system continues to operate for a considerable time **even during prolonged power cuts**, ensuring many more operations than traditional technologies.



SPEED, ACCELERATION AND DECELERATION WITH EXTREME ELEGANCE

The automation system with brushless digital technology creates perfect and elegant movements. With a constant **force and torque** at every point and with the option of varying the speed on deceleration and acceleration the system can be managed with maximum safety.



EXTREMELY LOW ENERGY CONSUMPTION

A motor that can operate at low voltage in super-intensive use and which can operate in environments with extremely demanding weather conditions while maintaining **very low energy consumption and absorption levels**.




DIGITAL AND VECTORIAL AUTOMATION CONTROLLER

The BRUSHLESS digital controller, which operates at low voltage **24V/36V DC**, allows 100% control of the automation system in digital mode. Due to its operation entirely based on a DSP microcontroller the travel and all the movements of your automation system can therefore be programmed and customised easily, precisely and elegantly.



MOTOR AT AMBIENT TEMPERATURE

The brushless motor was created with the main goal of being a motor for super intensive use and **with a 99% efficiency**. Regardless of how many operations the engine performs in a day, it always remains cold or at the most reaches the outside ambient temperature.



THE DIGITAL SILENCE OF THE MOTOR

One great impact is the **silence** or the near absence of noise, generated by the BRUSHLESS motor during all its movements.



MOTOR FOR SUPER-INTENSIVE USE

We wanted to surprise our customers with a product that was fundamentally different to any other product on the market. Fact: our motor remains **permanently cold** even after many days of super intensive use.



IMPACT, OBSTACLE DETECTION AND REVERSAL IN TOTAL SAFETY

Thanks to digital technology we are able to **detect an obstacle** and reverse the motor instantly, by simply specifying the torque of the motor, the sensitivity, the time and the travel of the reversal. All in full compliance with safety requirements.



ONBOARD NATIVE DIGITAL ENCODER

The BRUSHLESS motor has a highly advanced **native digital encoder** that controls management of automation systems in a safe, precise and extremely elegant manner.



SIMPLE INSTALLATION WITH A SINGLE 3-WIRE CABLE

The BRUSHLESS motor can be installed by simply connecting it using three wires! What could be easier? This will provide full digital management of your automation system thanks to the **SENSELESS** and **SENSED** (absolute encoder) technology incorporated in the BRUSHLESS sliding gate motors.




ADVANCED PRECISION ENGINEERING TO OBTAIN OPTIMAL MOTOR PERFORMANCE

We have created a mechanism that gives you the opportunity to get **the maximum performance out of the motor**. A product which combines the quality of the internal production processes, the mechanical processing and the use of high quality ferrous and non-ferrous materials.

BIONIK4

WHY BRUSHLESS?

STURDY AND ELEGANT, TO MANAGE ACCESSES TO CONDOMINIUMS,
COMMERCIAL PREMISES, INDUSTRIAL SITES AND RESIDENTIAL AREAS



BARRIER AVAILABLE
WITH BOOM UP TO 4 METERS

BIONIK, EQUAL ONLY TO ITSELF



1 DIGITAL 36V BRUSHLESS MOTOR
Innovative, revolutionary 36V Brushless digital motor with permanent magnetic field and a SENSORED digital technology encoder that permits unlimited use of the barrier with extremely reduced consumption and a mechanical absolute positioning system.

2 ADVANCED DIGITAL CONTROLLER
Easy to access, thanks to its position in the upper part of the barrier, well protected in the basket containing all the electronics, transformer compartment and support batteries. The digital controller ensures total, accurate management.

3 GEAR MOTOR WITH PERFECT GEARS
The gear motor is a mechanical jewel made entirely of aluminium, steel and bronze. All the gears are helicoidal with a 15° tilt, assembled on top quality bearings and inserted in perfectly machined seats to guarantee the absolute precision of the gear axes.

4 SMALL BUT HIGHLY RESISTANT STRUCTURE
The materials employed - steel and bronze - are top quality to ensure optimum robustness for the automation, making it highly stable during use. A vital role is also played by the surface treatment and the types of varnish, designed to make the barrier structure particularly resistant to a wide range of atmospheric agents.

5 LINKAGE LEVER AND SPRINGS
Different types of spring are available, according to the length of the boom and certified for millions of manoeuvres. Mechanical linkage lever with adjustable mechanical stops.

6 LED LIGHTING
Elegant LED lighting circuit all over the aluminium head of the barrier column. Can be configured via the control unit.

7 ABSOLUTE MECHANICAL POSITIONER
Powerful, innovative and accurate encoder with absolute positioning, mounted on the slow reducer shaft. Allows movements to be managed in tenths of a degree, and ensures perfect automation restart without relearning after the blackout or manual release phases.


8 ROBUST, ELLIPTIC BOOM
Aluminium boom with an elliptical section providing greater wind resistance, and central ribbing for even greater stability and robustness. Integrated signalisation LED on the upper side. Can be configured via the control unit.

9 ROBUST, INNOVATIVE RELEASE
Mechanical manual release with standard cylinder lock, able to unlock the barrier in any situation thanks to its excellent mechanics based on a twin-acting elliptical lever.

10 BIONIC BOOM SUPPORT ARM
Bionic support and protection arm in die-cast aluminium, directly connected to the reducer via a special system for pre-reducing the mechanical stress of the boom movement.

BIONIK1 BIONIK4HP BIONIK6 WHY BRUSHLESS?

STURDY AND ELEGANT, TO MANAGE ACCESSES TO COMMERCIAL AND INDUSTRIAL PREMISES AS WELL AS HEAVY TRAFFIC PARKING LOTS.



BARRIER AVAILABLE
WITH BOOM FROM 3 TO 6 METERS

BIONIK, EQUAL ONLY TO ITSELF

1 DIGITAL 36V BRUSHLESS MOTOR

Innovative, revolutionary 36V Brushless digital motor with permanent magnetic field and a SENSORED digital technology encoder that permits unlimited use of the barrier with extremely reduced consumption and a mechanical absolute positioning system.

2 ADVANCED DIGITAL CONTROLLER

Easy to access, thanks to its position in the upper part of the barrier, well protected in the basket containing all the electronics, transformer compartment and support batteries. The digital controller ensures total, accurate management.

3 GEAR MOTOR WITH PERFECT GEARS

A veritable mechanical "gem", the gear motor is made entirely of aluminium, steel and bronze. All gears are helicoidal with a 15° tilt, assembled on top quality bearings and inserted in perfectly machined seats to guarantee absolute precision of the gear axes. The take-off of the connecting shaft to the boom is of 45 mm.

4 HIGHLY RESISTANT STRUCTURE

The materials employed - steel and bronze - are top quality to ensure optimum robustness for the automation, making it highly stable during use. A vital role is also played by the surface treatment and the types of varnish, designed to make the barrier structure particularly resistant to a wide range of atmospheric agents.

5 LINKAGE LEVER AND SPRINGS

Different types of spring are available, according to the length of the boom and certified for millions of manoeuvres. Mechanical linkage lever with adjustable mechanical stops.

6 LED LIGHTING

Elegant LED lighting circuit all over the aluminium head of the barrier column. Can be configured via the control unit.

7 ABSOLUTE MECHANICAL POSITIONER

Powerful, innovative and accurate encoder with absolute positioning, mounted on the slow reducer shaft. Allows movements to be managed in tenths of a degree, and ensures perfect automation restart without relearning after the blackout or manual release phases.

8 ROBUST, ELLIPTIC BOOM

Elliptical section, wind-resistant aluminium boom with central ribbing, to provide even greater stability and sturdiness. Signalisation LED on both horizontal ends of the boom, integrated and configurable from the control unit.

9 ROBUST, INNOVATIVE RELEASE

Manual mechanical release by key, with European cylinder able to release the boom for any requirement and in any situation, thanks to its excellent mechanical features.


10 STURDY BOOM SUPPORT FLANGE

Extended cone double flange in die-cast aluminium for support and protection, directly connected to the reduction gear with 3 internal flanges fastening system, for a sturdy and safe mechanical movement of the boom.

BIONIK8

WHY BRUSHLESS?

STURDY AND ELEGANT, TO MANAGE ACCESSES TO COMMERCIAL PREMISES, INDUSTRIAL SITES AND LARGE LOGISTICS AREAS.



BARRIER AVAILABLE
WITH BOOM UP TO 8 METERS

BIONIK, EQUAL ONLY TO ITSELF

1 DIGITAL 36V BRUSHLESS MOTOR

Innovative, revolutionary 36V Brushless digital motor with permanent magnetic field and a SENSORED digital technology encoder that permits unlimited use of the barrier with extremely reduced consumption and a mechanical absolute positioning system. posizionamento assoluto meccanico.

2 ADVANCED DIGITAL CONTROLLER

Easy to access, thanks to its position in the upper part of the barrier, well protected in the basket containing all the electronics, transformer compartment and support batteries. The digital controller ensures total, accurate management.

3 GEAR MOTOR WITH PERFECT GEARS

A veritable mechanical "gem", the gear motor is made entirely of aluminium, steel and bronze. All gears are helicoidal with a 15° tilt, assembled on top quality bearings and inserted in perfectly machined seats to guarantee absolute precision of the gear axes. The take-off of the connecting shaft to the boom is of 55 mm.

4 HIGHLY RESISTANT STRUCTURE

The materials employed - steel and bronze - are top quality to ensure optimum robustness for the automation, making it highly stable during use. A vital role is also played by the surface treatment and the types of varnish, designed to make the barrier structure particularly resistant to a wide range of atmospheric agents.

5 STURDY BOOM SUPPORT FLANGE

Extended cone double flange in die-cast aluminium for support and protection, directly connected to the reduction gear for a sturdy and safe mechanical movement of the boom.

6 LED LIGHTING

Elegant LED lighting circuit all over the aluminium head of the barrier column. Can be configured via the control unit.

7 ABSOLUTE MECHANICAL POSITIONER

Powerful, innovative and accurate encoder with absolute positioning, mounted on the slow reducer shaft. Allows movements to be managed in tenths of a degree, and ensures perfect automation restart without relearning after the blackout or manual release phases.

8 ROBUST, ELLIPTIC BOOM

Elliptical section 4,100 mm aluminium Double Boom, wind resistant, with 2 strengthening telescopic inserts to fasten the boom to the flange and to connect the 2 booms through a dedicated aluminium double joint. Integrated signalisation LED on the upper side, configurable from the control unit.

9 ROBUST, INNOVATIVE RELEASE

Manual mechanical release by key, with European cylinder able to release the boom for any requirement and in any situation, thanks to its excellent mechanical features.


10 NEW DOUBLE SPRING LINKAGE LEVER

Innovative linkage lever with toothed insert, which guarantees a correct, double and millimetric adjustment of the balancing of the 2 x 85 mm diameter springs. Hooking of the double spring to the linkage lever with roller bearing for a better distribution of the boom load points, weights and stresses.

11 TELESCOPIC REINFORCED SUPPORTS

Two telescopic reinforced supports inside the boom, one for fastening to the support flange and the other for the joint between the two booms, 4,100 mm long, making the boom sturdy and safe.

BARRIER OVERVIEW



	RESIDENTIAL	COMMERCIAL	INDUSTRIAL	PARKING
BI/004				
BI/004/115				
BI/004HP				
BI/004HP/115				
BI/004HP/IS				
BI/004HP/IS/115				
BI/006				
BI/006/115				
BI/006/IS				
BI/006/IS/115				
BI/001PE				
BI/001PC				
BI/001PC/115				
BI/008				
BI/008/115				



Residential solution



Commercial solution



Industrial solution



Parking solution

TECHNICAL SPECIFICATIONS

	BI/004 - BI/004/115	BI/004HP - BI/004HP/115	BI/006 - BI/006/115	BI/008 - BI/008/115	BI/001PE	BI/001PC - BI/001PC/115
DESCRIPTION	BRUSHLESS 36V DC Barrier	BRUSHLESS 36V DC Barrier	BRUSHLESS 36V DC Barrier	BRUSHLESS 36V DC Barrier	BRUSHLESS 36V DC Barrier	BRUSHLESS 36V DC Barrier
						
BOOM	up to 4 m	up to 4 m	up to 6 m	up to 8,2 m	up to 3 m	up to 3 m
LINE POWER SUPPLY	230V AC - 115V AC 50/60Hz +-10%	230V AC - 115V AC 50/60Hz +-10%	230V AC - 115V AC 50/60Hz +-10%	230V AC - 115V AC 50/60Hz +-10%	230V AC 50/60Hz +-10%	230V AC - 115V AC 50/60Hz +-10%
BRUSHLESS MOTOR POWER SUPPLY	36V	36V	36V	36V	36V	36V
MAX POWER	220W	220W	220W	300W	450W	450W
FREQUENCY OF USE	Continuous	Super Intensive 	Super Intensive 	Super Intensive 	Super Intensive 	Continuous
OPERATING TEMPERATURE	-20 +55°C	-20 +55°C	-20 +55°C	-20 +55°C	-20 +55°C	-20 +55°C
DEGREE OF PROTECTION	IP54	IP54	IP54	IP54	IP54	IP54
OPEN TIME 90°	From 2 to 6 s (with boom up to 3 m) From 3 to 6 s (with boom up to 4 m)	From 3 to 6 s	From 4 to 8 s	From 9 to 29 s	From 2 to 4 s	From 1 to 3 s
ENCODER	Absolute digital encoder	Absolute digital encoder	Absolute digital encoder	Absolute digital encoder	Absolute digital encoder	Absolute digital encoder
TYPOLOGY ENCODER	Digital SENSORED	Digital SENSORED	Digital SENSORED	Digital SENSORED	Digital SENSORED	Digital SENSORED
ONBOARD CONTROL UNIT	CTRL	CTRL	CTRL	CTRL	CTRL/P	CTRL/P
DAILY OPERATION CYCLES (OPEN / CLOSE - 24 HOURS NON-STOP)	5000	5000	4000	2500	8000	12000
PACKAGED PRODUCT WEIGHT	47,5 kg	72 kg	74 kg	95 kg	72 kg	87,6 kg
DIMENSIONS	280 x 210 x 1.203 (L x P x H)	380 x 270 x 1237 (L x P x H)	380 x 270 x 1237 (L x P x H)	500 x 270 x 1237 (L x P x H)	380 x 270 x 1237 (L x P x H)	380 x 270 x 1237 (L x P x H)
RELEASE	Handle with a twin-acting elliptical lever and key with a STANDARD cylinder	Release of reduction gear on bearings, with European cylinder key	Release of reduction gear on bearings, with European cylinder key	Release of reduction gear on bearings, with European cylinder key	Release of reduction gear on bearings, with European cylinder key	Release of reduction gear on bearings, with European cylinder key
EXP B-CONNECT INPUT PREDISPOSITION	✓	✓	✓	✓	✓	✓
NUMBER OF PACKAGES PER PALLET	8	6	6	4	6	6



Brushless
Motor



Intensive
Use



High Speed
Motor



Reversible
Motor



PACKAGING BIONIK4

L.: 28 cm
W.: 21 cm
H. 120,3 cm

PACKAGING BIONIK1/4HP/6

L.: 38 cm
W.: 27 cm
H. 123,7 cm

PACKAGING BIONIK8

L.: 50 cm
W.: 27 cm
H. 123,7 cm



FUNCTIONS

OF AUTOMATED SLIDING GATE MOTOR

DESCRIPTION	BI/004 - BI/004/115	BI/004HP - BI/004HP/115
BOOM LENGHT	UP TO 4 M	UP TO 4 M
ONBOARD DIGITAL CONTROLLER	CTRL	CTRL
RADIO RECEIVER TYPE	H93/RX22A/I with fixed code connection H93/RX2RC/I with rolling code connection	H93/RX22A/I with fixed code connection H93/RX2RC/I with rolling code connection
MOTOR POWER SUPPLY	36V DC	36V DC
MOTOR MANAGEMENT TECHNOLOGY (ETC)	SENSORED technology	SENSORED technology
ENCODER TYPE	Magnetic Digital SENSORED, 4096 pulses per revolution	Magnetic Digital SENSORED, 4096 pulses per revolution
MAINS POWER SUPPLY	230V 50/60 Hz	230V 50/60 Hz
BATTERY OPERATION	(optional) 2 internal batteries 12V DC 4,5 Amp/h	(optional) 2 internal batteries 12V DC 4,5 Amp/h
ENERGY CONSUMPTION	Very low consumption	Very low consumption
NUMBER OF MOTORS	1	1
POWER SUPPLY FOR ACCESSORIES	24V DC	24V DC
FLASHING LIGHT BARRIER TYPE (INCLUDED)	24V DC LED	24V DC LED
FLASHING LIGHT BOOM TYPE	24V DC LED - Strip led, lenght 4 m	24V DC LED - Strip led, lenght 8 m
OUTPUT FOR BARRIER OPENING INDICATOR AND AUTOMATION SYSTEM ON WARNING LIGHT	√	√
OUTPUT FOR COURTESY LIGHT	40W	40W
TIMED AND GUARANTEED AUTOMATIC CLOSING	√	√
GATE EDGE SAFETY MANAGEMENT, 8.2KΩ OR STANDARD	√	√
LIMIT SWITCH TYPE	Adjustable open and closed position Mechanical travel limits	Adjustable open and closed position Mechanical travel limits
FORCE ADJUSTMENT IN NOMINAL MOVEMENT	√	√
FORCE ADJUSTMENT IN START-UP AND DECELERATION	√	√
OBSTACLE DETECTION (ALSO IN POSITION RECOVERY MODE) - MOTOR REVERSAL	√	√
OPENING AND CLOSING SPEED SETTING	√	√
DECELERATION DURING OPENING AND CLOSING	√	√
OPENING AND CLOSING APPROACH DISTANCE SETTING	√	√
STARTING ACCELERATION (SOFT-START) FOR OPENING AND CLOSING MANOEUVRES	√	√
SAFEGUARDED CLOSURE/OPENING FUNCTION	√	√
STOPPING SPACE AND MOTOR BRAKING	√	√
PARTIAL OPENING CONTROL MASTER/SLAVE MODE	√	√
HUMAN PRESENCE CONTROL	√	√
CONDOMINIUM FUNCTION	√	√
SAFETY DEVICE CONFIGURATION	√	√
INSTALLATION TEST FUNCTION	(prog button)	(prog button)
OPERATING TEMPERATURE	-20°C/+55°C	-20°C/+55°C
INVERTER THERMAL PROTECTION	√	√
MAGNETIC ELECTRO-LOCK MANAGEMENT	(optional) √	(optional) √
DETECTOR LOOP MANAGEMENT	(optional) √	(optional) √
CLOCK FUNCTION (INCLUDED)	√	√
PARKING ACCESS MODE FUNCTION (INCLUDED)	√	√
EXTERNAL STATUS TYPE OUTPUT SETTING	(optional) √	(optional) √
RESTORE FACTORY DEFAULT VALUES	√	√
INFORMATION ON USE OF MOTOR	√	√
SECURITY PASSWORD MANAGEMENT	√	√
ENABLING OF ANTI-BREAKING THROUGH SYSTEM	√	√

DIMENSIONS



BIONIK4
 BI/004
 BI/004/115





BIONIK1
 BI/001PE

BIONIK4HP
 BI/004HP
 BI/004HP/115
 BI/004HP/IS
 BI/004HP/IS/115



BIONIK6
 BI/006
 BI/006/115
 BI/006/IS
 BI/006/IS/115



BIONIK1
BI/001PC
BI/001PC/115



BIONIK8
BI/008
BI/008/115





R99/BASB20 Pack of 20 stickers for barrier

BI/004
BI/004HP
BI/004HP/115
BI/004HP/IS
BI/004HP/IS/115
BI/006
BI/006/115
BI/006/IS
BI/006/IS/115
BI/001PE
BI/001PC
BI/001PC/115
BI/008
BI/008/115

✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓



RL670 European cylinder key for release system series SMARTY - BIONIK

✓



SND/BA/68/DW Articulated joint 90° with lower tie rod for boom arms BA/68

✓



SND/BA/68/UP Articulated joint 90° with upper tie rod for boom arms BA/68

✓



SND/BA/68/UP/RD Articulated joint 90° with upper tie rod (lowered version) for boom arms BA/68

✓



SND/BA/90/DW Articulated joint 90° with lower tie rod for boom arms BA/90

✓ ✓ ✓



SND/BA/90/UP Articulated joint 90° with upper tie rod for boom arms BA/90

✓ ✓ ✓



SP/48/01 Spring diameter 48 mm for barriers

✓



SP/61/01 Spring diameter 61 mm for barriers

✓



SP/72/01 Spring diameter 72 mm for barriers

✓ ✓ ✓ ✓ ✓



SP/83/01 Spring diameter 83 mm for barriers

✓ ✓ ✓ ✓



SP/85/01 Spring diameter 85 mm for barriers

✓ ✓




SP/85/AS/02 Assembly 2 spring diameter 85 mm for barriers

✓

BIONIK

THE BRUSHLESS AUTOMATIC BARRIER
FROM DIGITAL THINKING




25



Illuminated and moving boom barrier

STANDARD INSTALLATION


A PRACTICAL EXAMPLE FOR YOUR SUCCESSFUL INSTALLATION



27



AUTOMATIC BARRIER





PREMIUM DEALER / PROFESSIONAL DEALER

